

Fire Rating	Type I	Type II	Maximum Daylite Openings			Additional Information
			Single	Double	Lite	
20 Minute	Yes	Yes	3'0" x 9'0"	6'0" x 9'0"	----	
20 Minute Sidelite	Yes	Yes	see above	----	2'0" x 8'10-1/2"	
20 Minute Borrowed Lite	Yes	Yes	----	----	4'0" x 9'0"	
20 Minute Borrowed Lite	Yes	Yes	----	----	5'0" x 5'0"	
20 Minute Positive Pressure	No	Yes	*4'0" x 9'0"	*6'0" x 9'0"	----	UBC 7-2/UL10C - see below
45 Minute	No	Yes	3'0" x 9'0"	6'0" x 9'0"	----	
90 Minute Positive Pressure	No	Yes	4'0" x 9'0"	8'0" x 9'0"	----	Min. 3-5/8" thru Max 7-7/8" throat size
Frequency	Yes	Yes	3'0" x 9'0"	----	----	100,000 cycle swing test

**All fire ratings listed are neutral/negative pressure, unless noted otherwise.**

**\*20 Minute Positive Pressure**

Door frame supplied with Pemko PK4 gasket in the door stop (only available in black and white).

Pemko intumescent hot smoke seal HSS1000 or HSS2000 must be installed also. Not supplied by Frameworks.

**Adjustable Frames**

Type 2, 90 minute positive pressure

Type 2, 20 minute positive pressure