

FRAME SYSTEM COMPARISON

	TYPE II FRAME SYSTEM			TYPE I FRAME SYSTEM		
Design	Rectilinear			Rectilinear		
Face Profile	1½" or 2"			1½"		
Return	9/32"					
Snap-on Trim	1¼" 1½" 2"					
Wall Thickness	.062"			.062"		
Throat Sizes	3½" 3¾" 4⅝" 4⅞" 5¼" 5½" 6⅛" 7¼"			3¾" 4⅞"		
FIRE RATINGS	RATING	MIN THROAT	MAX SIZE	RATING	MIN THROAT	MAX SIZE
Door Frame	20 Min*	3½"	3090 (WHI-495-0817) 6090 (WHI-495-0894)	20 Min*	3¾"	3090 (WHI-495-0817) 6090 (WHI-495-0823)
	45 Min	3½"	3090 (WHI-495-0965) 6090 (WHI-495-0965)			
	90 Min	3 5/8"	3090 (WHI-495-1424) 6090 (WHI-495-1424)			
Door Frame with Sidelight	20 Min	3½"	3090 DF (WHI-495-0893) 2090 SL (WHI-495-0893)	20 Min	3¾"	3090 DF (WHI-495-0963) 2090 SL (WHI-495-0963)
Borrowed Light	20 Min	3½"	5050 (WHI-495-0964) 4090 (WHI-495-0964)	20 Min	3¾"	5050 (WHI-495-0964) 4090 (WHI-495-0964)

* Positive and negative pressure

NOTE: 45 minute ratings can be achieved with fixed throat sizes. 20 minute and 90 minute rating can be achieved with fixed or adjustable throat sizes

3⅝" to 7⅞".